SC650

Comfort and convenience. Say hello to the new SC650



NILFISK

Flexible and safe cleaning in areas with people in close proximity

Highly manoeuvrable, user-friendly cleaning

Optimised for easy handling

The SC650 features improved versatility, up to 30% greater productivity, better-than-ever reliability, extremely silent operation, and the most advanced ergonomics available. Designed with cleaning convenience and productivity in mind, the SC650 is highly versatile, featuring a user interface that is suitable for users of any level. The SC650 is ideal for use in retail, institution, hospitality, healthcare, and logistics centres.



Clean anytime without interruption

Energy-saver with advanced ergonomics

Clean effectively and manage resource consumption as select versions of the SC650 come equipped with EcoFlex™. Instantly, with the press of a button activate this 60-second power-cleaning function and receive a short-term water, detergent output, and brush pressure boost for instant removal of tough debris, and thorough cleaning of extra-dirty floor areas.



Easy-to-use and comfortable the SC650 features OneTouch™ technology and a highly intuitive user interface and large LCD display. Designed with user comfort, convenience and productivity in mind, the SC650, with drive paddle operation is a highly versatile machine that is suitable for users of any level.

Carefree maintenance The SC650 scrubber dryer is easy to service, while saving on costs. We provide a global fleet of service professionals, as well as comprehensive product training. Our partnership includes fast, worldwide parts accessibility, along with first-rate servicing to keep your machine running optimally, while minimising potential downtime.

Optimise water and detergent use by determining your solution flow based on the speed of your machine with SmartFlow™ technology. Ensure consistent cleaning results and provide your operator with the confidence to efficiently get the job done.



Ideal for safe, efficient cleaning

Compatibility with a variety of power sources including Lead, and lithium-ion batteries.

Technical specifications

Description	Unit	SC650 66D	SC650 71D	SC650 85D	SC650 71C
Scrub deck type		Dual disc	Dual disc	Dual disc	Dual cylindrical
Cleaning width	mm	660	710	837	703
Productivity rate theoretical	m²/h	3996	3976	4687	3937
Min. aisle turn	mm	192	203	245	242
Rated power	W	1400	1400	1400	1800
Solution / recovery tank capacity	L	80	80	80	80
Dimension (width x length x height)	mm	748x1500x1072	748x1500x1072	860x1574x1072	785x1472x1072
Sound pressure level / silent mode (ISO 11201, ISO 4871) (LpA)	dB(A)	65/63 ± 3	66/64 ± 3	67/65 ± 3	70/69 ± 3
Vibration level at the operator's arms (ISO 5349-1)	m/s²	< 2.5 m/s²	< 2.5 m/s²	< 2.5 m/s²	< 2.5 m/s²
Max speed	km/h	5.6	5.6	5.6	5.6
Weight (GVW)	kg	346	347	353	351

10445 11/2023

Nilfisk Ltd
Nilfisk House, Bowerbank Way,
Gilwilly Industrial Estate, Penrith, Cumbria, CA11 9BQ
Tel: 01 294 3838 · sales.uk@nilfisk.com
www.nilfisk.ie

NILFISK